DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

Reference number of the declaration of performance:	IN 52050002		
Unique identification code of the product-type:	MC-AnchorSolid E820 Injection system for use in concrete		
Intended use:	Bonded anchor for use in uncracked concrete		
Manufacturer:	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop		
System of AVCP:	System 1		
Harmonised standard:	European Assessment DocumentETAG 001, Part 5 (Edition 04-2013)European Technical Assessment:ETA-15/0506 (29.01.2016)Technical Assessment Body:DIBt – Deutsches Institut für Bautechnik		
Notified body:	2323 – IEA GmbH & Co. KG, Stuttgart		
Declared performances:	Mechanical resistance and stability (BV	echanical resistance and stability (BWR 1)	
	Essential characteristic	Performance	
	Characteristic resistance tension and shear loads, displacements	See Annex C1 to C4, ETA-15/0506	
Safety in case of fire (BWR 2)			
	Essential characteristic	Performance	
	Reaction to fire	Anchorages satisfy requirements for Class A1	
	Resistance to fire	NPD	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen Head of research and development and quality control



Bottrop, 17.04.2019 (place and date of issue)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.