DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

| Reference number of the declaration of performan | | | | |
|----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|
| Unique identification code of the product-type: MC-DUR 1212 VB | | | | |
| Intended use: | Surface protection products – Coating Protection against ingress (1.3) Moisture control (2.2) Physical resistance (5.1) Increasing resistivity (8.2) | | | |
| | Synthetic resin screed for internal uses | | | |
| Manufacturer: | MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop | | | |
| System of AVCP: | System 2+ (for uses in buildings and civil engineering works) System 4 (for internal uses) | | | |
| Harmonised standard: | EN 1504-2:2004 EN 13813:2002 | | | |
| Notified body: | Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) Identification no: 0754 | | | |

Declared performances:

| Essential characteristics | Performance | Harmonised technical specification | |
|------------------------------------------|-----------------------------------------------------|------------------------------------|--|
| Compressive strength | class II (≥ 50 N/mm²) | | |
| Abrasion resistance | < 3000 mg | | |
| Permeability to CO ₂ | <i>s</i> _D > 50 m | EN 1504-2:2004 | |
| Water vapour permeability | class II |] | |
| Capillary absorption and permeability to | <i>w</i> < 0,1 kg/m ² x h ^{0,5} | | |

| Essential characteristics | Performance | Harmonised technical specification |
|------------------------------------|---------------------------------------------|------------------------------------|
| water | | |
| Impact resistance | class III (≥ 20 Nm) | |
| Adhesion strength by pull-off test | ≥ 1,5 (1,0) ¹⁾ N/mm ² | |
| Reaction to fire | class E _{fl} | |
| Release of dangerous substances | EN 1504-2, Pkt. 5.3 | |

¹⁾The value in brackets is the lowest accepted value of any reading

| Essential characteristic | Performance | Harmonised technical specification |
|---------------------------------|-------------------|------------------------------------|
| Reaction to fire | Efl ^{a)} | |
| Release of corrosive substances | SR | |
| Wear resistance | AR1 | EN 13813:2002 |
| Bond strength | B1,5 | |
| Impact resistance | IR20 | |

a) According to Commission Decision 2010/85/EU of 9 February 2010 the product fulfils the reaction-to-fire performance class E/Efl without further testing

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Bottrop, 23.03.2016 (place and date of issue)

Dr. Hans-Günter Seltmann Head of research and development and quality control

KLARUN

(signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.

