

# DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

---

**Reference number of the  
declaration of performance:**

IN 553100024

---

**Unique identification code of  
the product-type:**

MC-Injekt 2133 flex (P)

---

**Intended use:**

Concrete injection for ductile filling of cracks, voids and  
interstices (D)  
U (D1) W (3) (1/2/3/4) (5/40)

---

**Manufacturer:**

MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
46238 Bottrop

---

**System of AVCP:**

System 4

---

**Harmonised standard:**

EN 1504-5:2004

---

**Notified body:**

Not relevant

---

**Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Adhesion	> 0.1 N/mm <sup>2</sup>	EN 1504-5
Elongation	> 10 %	
Water tightness	D1 (2x 10 <sup>5</sup> Pa)	
Viscosity	800 mPas*s	
Injectability into dry medium	Class 0.3 (0.3 mm)	
Injectability into nondry medium	Class 0.3 (0.3 mm)	
Compatibility with concrete	NPD	
Corrosion behaviour	It is assumed that there are no corrosive effects.	
Release of dangerous substances	In accordance with EN 1504-5, section 5.4	

<sup>1)</sup> The value in brackets is the lowest accepted value of any reading

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen  
Head of research and development and quality control



Bottrop, 15.05.2019  
(place and date of issue)

.....  
(signature)

**Annex**

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.