

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

**Reference number of the
declaration of performance:**

IN 5527001

**Unique identification code of
the product-type:**

MC-Injekt 2700 L (P)

Intended use:

Concrete injection for ductile filling of cracks, voids and
interstices (D)
U (F1) W (2) (1) (5/40) (0)

Manufacturer:

MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
46238 Bottrop

System of AVCP:

System 4

Harmonised standard:

EN 1504-5:2004

Notified body:

-

Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Adhesion	> 3 N/mm ²	EN 1504-5:2004
Volumetric shrinkage	< 3 %	
Glass transition temperature	> 40 °C	
Injectability into dry medium	0.2 mm	
Durability (Compatibility with concrete)	NPD	
Release of dangerous substances	EN 1504-5, Art. 5.4	


a) Pursuant to Commission Decision 2010/85 / EU of 09.02.2010, the product complies with fire classification E, without that an examination is required.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen
Head of research and development and quality control

Bottrop, 16.02.2021
(place and date of issue)


.....
(signature)



Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.