

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

Reference number of the
declaration of performance: IN4426000

Unique identification code of the product-type: Nafufill KM 220

Intended use: **Product for non-structural repair for concrete**
Applying mortar by hand (3.1)
Spraying concrete or mortar (3.3)

Manufacturer: MC-Bauchemie Müller GmbH & Co.KG
Am Kruppwald 1-8
46238 Bottrop

System of AVCP: System 2+ (for uses in buildings and civil engineering works)

Harmonised standard: EN 1504-3:2005

Notified body: Institut für Massivbau und Baustofftechnologie
Universität Karlsruhe (TH)
Identification no: 0754

Declared performances:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Compressive strength	class R2	System 2+	EN 1504-3:2005
Chloride ion content	≤ 0.05 %		
Adhesive bond	≥ 0.8 MPa		
Thermal compatibility Freeze-thaw	≥ 0.8 MPa		
Thermal compatibility Thunder shower	≥ 0.8 MPa		
Restrained shrinkage/expansion	≥ 0.8 MPa		
Carbonation resistance	passed		
Reaction to fire	class E		


Dangerous substances	EN 1504-3, Pkt. 5.4		
----------------------	---------------------	--	--


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen
Head of research and development and quality control

Bottrop, 26.05.2020
(place and date of issue)


.....
(signature)



Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is attached to this Declaration of Performance.